

*Different Class Products of Korea*

# Slush Machine

Slush Machine  
Multi-purpose ALL IN ONE



# ICETRO Smoothie & Slush Machine

*It's so  
delicious!*



## SLUSH MACHINE - 12LITER CAPACITY


- Unbreakable & non-poisonous P.C 12liter(3.17gallon) capacity bowl.  
(Maximum mix capacity is 9liter.)
- Stainless steel body and case for long life.
- Durable metal geared motor for long life and reliability.
- TC & Torque control system.



Drain cap



Drip guidance



Air filter



Drain box



**SSM-180**

- Tank capacity : 12Liter(3.17gallon) X 1
- Weight : 30Kg (66.2 lbs)

## SLUSH MACHINE - 7.5LITER CAPACITY

- Perfect performance in tropical zone.
- Fastest Freezing ability.
- Unbreakable & non-poisonous P.C 7.5liter(1.98gallon) capacity bowl.
- TC & Torque control system. [Drain cap] [Drip guidance] [Air filter] [Drain box]



Locking hole



Leveler



**SSM-52**

- Tank capacity : 7.5Liter(1.98gallon) X 2
- Weight : 38Kg (83.8 lbs)



Display light

**SSM-280**

- Tank capacity : 12Liter(3.17gallon) X 2
- Weight : 52Kg (114.7 lbs)



**SSM-420**

- Tank capacity : 12Liter(3.17gallon) X 3
- Weight : 80Kg (176.4 lbs)



**SSM-560**

- Tank capacity : 12Liter(3.17gallon) X 4
- Weight : 160Kg (352.8 lbs)

## Multi-Purpose ALL IN ONE

**Slush & Soft Ice Cream Machine** are combined.

You can enjoy Slush & Yogurt together.



**SSM-280**

- Tank capacity : 12Liter(3.17gallon) X 2
- Weight : 52Kg (114.7 lbs)

Combined

&



**SSI-151TG**

- Cylinder capacity : 1.4Liter(0.37gallon) X 1
- Weight : 90Kg (198 lbs)



**ALL IN ONE**

**NEW**  
LCD SLUSH MACHINE

## ISM-72L



CLASSIFICATION		SPECIFICATION
MODEL		ISM-72L (FROZEN BEVERAGE)
PRODUCT NAME		SLUSH MACHINE
BODY	SIZE(WXDxH) / mm	410 X 430 X 730 (Including Cover)
	SIZE(WXDxH) / Inch	16.1x16.9x28.7 (Including Cover)
Electrical Features	Power Consumption	500W
	Running Current	3.6A
	Gear Motor	2EA
	Fan Motor	10W
Freezing	Compressor	Fully Closed
	Condenser	Pin tube type
	Evaporator	Drum TyPE
	Cooling Type	Capillary Tube
	Refrigerant	R-134A
Miscellaneous	Proper Material Quantity	3.0L X 2TANK (Maximum 5L)
	Control Method	LCD BUTTON, MICOM CONTROL
	Operation Environment	Ambient Temperature: 10~38°C Voltage Rating: 115V/60Hz, 208~230V/60Hz, 220~240V/50Hz



### SSM-180

Dimensions (W x D x H)	195x487x837(mm) 7.7x19.2x33.0(inch)
Weight	30Kg (66.2lbs)
Legs	Rubber Packing
Power consumption	320W
Gear Motor	67Wx1EA
Refrigerant	R-134a
Compressor	0.35HP
Voltage Rating	115V/60Hz, 208~230V/60Hz, 220~240V/50Hz
Operation accessories	-



### SSM-280

Dimensions (W x D x H)	395x468x897(mm) 15.6x18.5x35.4(inch)
Weight	51Kg (112.5lbs)
Legs	Rubber Packing
Power consumption	1,020W
Gear Motor	67Wx2EA
Refrigerant	R-404a
Compressor	0.85HP
Voltage Rating	115V/60Hz, 208~230V/60Hz, 220~240V/50Hz
Operation accessories	Supporting Table



### SSM-420

Dimensions (W x D x H)	598x468x897(mm) 23.6x18.5x35.4(inch)
Weight	75Kg (165.4lbs)
Legs	Rubber Packing
Power consumption	1,350W
Gear Motor	67Wx3EA
Refrigerant	R-404a
Compressor	0.85HP(50Hz spec),1.30HP(60Hz spec)
Voltage Rating	115V/60Hz, 208~230V/60Hz, 220~240V/50Hz
Operation accessories	Supporting Table



### SSM-560

Dimensions (W x D x H)	795x502x1,307(mm) 31.3x19.8x51.5(inch)
Weight	160Kg (352.8lbs)
Legs	Casters
Power consumption	2,040W
Gear Motor	67Wx4EA
Refrigerant	R-404a
Compressor	0.85HPx2EA
Voltage Rating	208~230V/60Hz, 220~240V/50Hz
Operation accessories	Supporting Table



### SSM-52

Dimensions (W x D x H)	420x380x705(mm) 16.6x7.1x27.8(inch)
Weight	38Kg (83.8lbs)
Legs	Adjustable leveler
Power consumption	500W
Gear Motor	67x2EA
Refrigerant	R134a
Compressor	0.5HP
Voltage Rating	115V/60Hz, 208~230V/60Hz, 220~240V/50Hz



### ALL IN ONE

Dimensions (W x D x H)	825x724x1,500(mm) 32.5x28.5x59.1(inch)
Weight	190Kg (419lbs)
Slush Part : Same as SSM-280	
Soft Ice Cream Part : Same as SSI-151TG	
Mix Hopper Capacity	10liter (2.65gallon)
Cylinder Capacity	1.4liter (0.37gallon)
Dasher Motor	0.37KW
Maximum Production	12Kg/h(26.5lbs/h)
First Dispensing Time	6~8min
Consecutive Dispensing	5~6cups(100cc/3.5oz)
Compressor-Cylinder	0.85HP(R404a)
Compressor-Mix	0.35HP(R134a)
Voltage Rating	208~230V/60Hz, 220~240V/50Hz

\*The product's design and specification is subject to change without prior notice.

Manufactured by:



54-7 Road, Gumdan-Ro, Seo-ku, Incheon, Korea  
TEL : +82-32-814-2160 FAX : +82-32-814-1798  
Website : www.icetro.com  
E-mail : sales@icemaker.co.kr

Distributed by :

